



## CARACTERÍSTICAS GERAIS

Em conformidade com a norma EN 61439-3

Para montagem saliente

Fabricados em termoplástico

Cor: branco RAL 9010

Porta opaca, reversível e com abertura a 180°

Instalação de equipamentos em calha (35 mm) EN50022

Espaço de 20 mm entre calha e o fundo da caixa para passagem de cabos

Com entradas métricas pré-marcadas

Características mecânicas: material poliestireno

Tensão de isolamento 400V. Tensão nominal AC 230/400V.

Humidade máxima (50%HR a + 40°C)

Classe II de isolamento

IP40/IK07

Sem halogéneos

Acessórios incluídos:

Equipado com ligador T/N, Ref.:SL16N16T


Etiqueta para identificação do circuito

Opção:

Cor cinza RAL 7035

Ligador rápido fixconnect

## CARACTERÍSTICAS TÉCNICAS



|                                                |                           |
|------------------------------------------------|---------------------------|
| Marca                                          | TEV                       |
| Icons                                          |                           |
| EF000003 - Mounting method                     | Surface mounted (plaster) |
| EF000266 - Number of rows                      | 3                         |
| EF002950 - Width in number of modular spacings | 36                        |
| EF000339 - Type of cover                       | Door                      |
| EF009212 - Cover model                         | Closed                    |
| EF006244 - Transparent cover/door              | false                     |
| EF001596 - Material housing                    | Plastic                   |
| EF000040 - Height                              | 514 mm                    |
| EF000008 - Width                               | 263 mm                    |
| EF000049 - Depth                               | 113 mm                    |
| EF015776 - Earthing terminal block             | true                      |
| EF015777 - Neutral terminal block              | true                      |
| EF001134 - DIN-rail                            | true                      |
| EF000118 - With mounting plate                 | false                     |
| EF000007 - Colour                              | White                     |
| EF000116 - RAL-number                          | 9010                      |
| EF005474 - Degree of protection (IP)           | IP40                      |
| EF006306 - With lock                           | false                     |
| EF004462 - Type of closure                     | Other                     |