



#### CARACTERÍSTICAS GERAIS

Em conformidade com a norma EN 60670-1  
Para montagem saliente  
Fabricadas em material isolante termoplástico  
Cor cinzento RAL 7035  
Tampa com aperto por encaixe  
Inclui 6 entradas e 6 buçins cónicos (tipo SD20)  
Entradas/saídas: cabos flexíveis e tubos lisos  
Tensão de isolamento 500V  
Classe II de isolamento  
IP55/IK07  
Sem halogéneos

## CARACTERÍSTICAS TÉCNICAS



|                                         |                        |
|-----------------------------------------|------------------------|
| Marca                                   | TEV                    |
| Icons                                   |                        |
| EF004969 - Max. conductor cross section | 6 mm <sup>2</sup>      |
| EF000557 - Equipped with                | Other                  |
| EF000051 - Shape                        | Square                 |
| EF000003 - Mounting method              | Wall-/ceiling mounting |
| EF012570 - Mounting in the soil         | false                  |
| EF012571 - Mounting under water         | false                  |
| EF005496 - For tube diameter            | Other                  |
| EF005604 - Inlet from the rear          | false                  |
| EF001438 - Length                       | 88 mm                  |
| EF000008 - Width                        | 88 mm                  |
| EF000049 - Depth                        | 48 mm                  |
| EF006169 - Tackable                     | false                  |
| EF003593 - Number of inlets             | 6                      |
| EF007661 - Type of housing feed-through | Trimable step membrane |
| EF002169 - Material                     | Plastic                |
| EF000025 - Halogen free                 | true                   |
| EF000139 - Surface protection           | Untreated              |
| EF000007 - Colour                       | Grey                   |
| EF005474 - Degree of protection (IP)    | IP55                   |
| EF009212 - Cover model                  | Other                  |
| EF011401 - Transparent cover            | false                  |
| EF004586 - Cover attachment             | Snapped on             |
| EF009476 - Castable                     | false                  |
| EF009477 - With casting compound        | false                  |
| EF001454 - Sealable                     | false                  |
| EF001613 - Circuit integrity            | None                   |
| EF005032 - With screening               | false                  |
| EF005436 - Weatherproof                 | false                  |
| EF001742 - Operating temperature        | -25 a 40 °C            |
| EF004191 - Explosion-tested version     | false                  |
| EF005728 - For Ex-zone gas              | None                   |
| EF008404 - For Ex-Zone dust             | None                   |