




CARACTERÍSTICAS GERAIS

Em conformidade com a norma EN 60670-1
Para montagem saliente
Fabricadas em material isolante termoplástico
Cor cinzento RAL 7035
Tampa com aperto por parafuso com posição 0/1
Inclui 5 entradas e 5 buçins cónicos (tipo SD25)
Entradas/saídas: cabos flexíveis e tubos lisos
Tensão de isolamento 500V
Classe II de isolamento
IP55/IK07
Sem halogéneos

CARACTERÍSTICAS TÉCNICAS



Marca	TEV
Icons	
EF004969 - Max. conductor cross section	6 mm ²
EF000557 - Equipped with	Other
EF000051 - Shape	Square
EF000003 - Mounting method	Wall-/ceiling mounting
EF012570 - Mounting in the soil	false
EF012571 - Mounting under water	false
EF005496 - For tube diameter	Other
EF005604 - Inlet from the rear	false
EF001438 - Length	116 mm
EF000008 - Width	116 mm
EF000049 - Depth	60 mm
EF006169 - Tackable	false
EF003593 - Number of inlets	5
EF007661 - Type of housing feed-through	Trimable step membrane
EF002169 - Material	Plastic
EF000025 - Halogen free	true
EF000139 - Surface protection	Untreated
EF000007 - Colour	Grey
EF005474 - Degree of protection (IP)	IP55
EF009212 - Cover model	Other
EF011401 - Transparent cover	false
EF004586 - Cover attachment	Other
EF009476 - Castable	false
EF009477 - With casting compound	false
EF001454 - Sealable	true
EF001613 - Circuit integrity	None
EF005032 - With screening	false
EF005436 - Weatherproof	false
EF001742 - Operating temperature	-25 a 40 °C
EF004191 - Explosion-tested version	false
EF005728 - For Ex-zone gas	None
EF008404 - For Ex-Zone dust	None