



CARACTERÍSTICAS GERAIS

Em conformidade com a norma EN 61439-3

Para montagem saliente

Fabricado em termoplástico

Cor: branco RAL 9010

Cobertura frontal equipada com parafusos $\frac{1}{4}$ de volta

Instalação de equipamentos em calha (35 mm) EN50022

Características mecânicas: material poliestireno

Tensão de isolamento 400V

Humidade máxima (50%HR a + 40°C)

Classe II de isolamento

IP40/IK07

Sem halogéneos


Acessórios incluídos:

Equipado com ligador T/N - ref: SL16N16T

Etiqueta para identificação do circuito

Tampas de vedação

CARACTERÍSTICAS TÉCNICAS



Marca	TEV
Icons	
EF000003 - Mounting method	Surface mounted (plaster)
EF000266 - Number of rows	2
EF002950 - Width in number of modular spacings	24
EF000339 - Type of cover	Cover
EF009212 - Cover model	With notch
EF006244 - Transparent cover/door	false
EF001596 - Material housing	Plastic
EF000040 - Height	385 mm
EF000008 - Width	280 mm
EF000049 - Depth	85 mm
EF015776 - Earthing terminal block	true
EF015777 - Neutral terminal block	true
EF001134 - DIN-rail	true
EF000118 - With mounting plate	false
EF000007 - Colour	White
EF000116 - RAL-number	9010
EF005474 - Degree of protection (IP)	IP40
EF006306 - With lock	false
EF004462 - Type of closure	Other