



EAN: 5607353026012

Emb.: 1

Peso Líquido: 7kg

CARACTERÍSTICAS GERAIS

Complies with standard EN 61439-3

For flush mounting, EDP switchboard version

Made from thermoplastic

Color: white RAL 9010

Reversible metal door with 180° opening

Double rotary lock

Chassis removable in rail (35 mm) EN50022

With pre-marked metric inputs

Insulation voltage 400V. Nominal AC voltage 230/400V. Maximum humidity (50%HR at + 40°C)

When installed with the BM125 splitter, allows operating currents of up to 125A

Class II insulation

IP54/IK07

Halogen-free

Accessories included:

Equipped with T/N connector

Label for circuit identification

Option:

Fixconnect quick connector

CARACTERÍSTICAS TÉCNICAS

Brand	TEV
Icons	
Cor	No
EF000003 - Mounting method	Flush mounted (plaster)
EF000266 - Number of rows	4
EF002950 - Width in number of modular spacings	58
EF000339 - Type of cover	Door
EF009212 - Cover model	With notch
EF006244 - Transparent cover/door	false
EF001596 - Material housing	Plastic
EF000040 - Height	805 mm
EF000008 - Width	435 mm
EF000049 - Depth	141 mm
EF000218 - Built-in depth	125 mm
EF015776 - Earthing terminal block	true
EF015777 - Neutral terminal block	true
EF001134 - DIN-rail	true
EF000118 - With mounting plate	true
EF000007 - Colour	White
EF000116 - RAL-number	9010
EF005474 - Degree of protection (IP)	IP54
EF006306 - With lock	false
EF004462 - Type of closure	Cylinder