



CARACTERÍSTICAS GERAIS

Em conformidade com a norma EN 61439-3

Para montagem de embutir

Fabricado em termoplástico

Cor: branco RAL 9010

1 fila, 14 módulos

Porta metálica e fecho rotativo, porta com aro reversível

Instalação de equipamentos em calha DIN (35 mm) EN50022

Características mecânicas: material poliestireno

Tensão de isolamento 400V

Humidade máxima (50%HR a + 40°C)

Classe II de isolamento

IP41/IK07

Sem halogéneos

Acessórios incluídos:

Equipado com ligador T/N - Ref: SL16N16T


Etiqueta para identificação do circuito

Opção:

Cor cinza RAL 7035

Ligador rápido fixconnect

CARACTERÍSTICAS TÉCNICAS



Marca	TEV
Icons	
EF000003 - Mounting method	Flush mounted (plaster)
EF000266 - Number of rows	1
EF002950 - Width in number of modular spacings	14
EF000339 - Type of cover	Door
EF009212 - Cover model	Closed
EF006244 - Transparent cover/door	false
EF001596 - Material housing	Plastic
EF000040 - Height	320 mm
EF000008 - Width	358 mm
EF000049 - Depth	94 mm
EF000218 - Built-in depth	89 mm
EF015776 - Earthing terminal block	true
EF015777 - Neutral terminal block	true
EF001134 - DIN-rail	true
EF000118 - With mounting plate	false
EF000007 - Colour	White
EF000116 - RAL-number	9010
EF005474 - Degree of protection (IP)	IP41
EF006306 - With lock	false
EF004462 - Type of closure	Cylinder