

Duplo Isolamento unknown



CARACTERÍSTICAS GERAIS

Em conformidade com a norma EN 60670-1

Para montagem de embutir

Fabricada em material isolante termoplástico

Cor: verde RAL 6018

Entradas/saídas: cabos flexíveis e tubos lisos ou corrugados


Meios de fixação: Garra de aperto rápido

Classe II de isolamento na versão com tampa

IP20/IK07 e IP40/IK07 na versão com tampa

Sem halogéneos

CARACTERÍSTICAS TÉCNICAS



Marca	TEV
Icons	IP20, IK07, RAL6018, Duplo Isolamento
EF000003 - Mounting method	Hollow wall
EF000051 - Shape	Round
EF000767 - Construction type	Cable junction box
EF000010 - Model	Single
EF009204 - Provided with revolving ring	false
EF001229 - Connectable	true
EF000557 - Equipped with	Clamp
EF000551 - Diameter	65 mm
EF000049 - Depth	50 a 50 mm
EF004702 - For number of electric fittings	1
EF004508 - Mounting switching equipment	Screw or spread out
EF005066 - With screws	true
EF009763 - Housing feed-through by break-out opening	true
EF009206 - Housing feed-through by seal membrane	false
EF009207 - Housing feed-through by nozzle	false
EF009208 - Housing feed-through by step membrane	false
EF005496 - For tube diameter	20 mm
EF005466 - Suitable for cable diameter	1,5 a 2,5 mm
EF005657 - Pipe locking	false
EF009209 - Pipe locking optional	false
EF005604 - Inlet from the rear	true
EF003593 - Number of inlets	8
EF002169 - Material	Plastic
EF000025 - Halogen free	true
EF000139 - Surface protection	Untreated
EF000007 - Colour	Green
EF005474 - Degree of protection (IP)	IP20
EF009212 - Cover model	None
EF011401 - Transparent cover	false
EF004586 - Cover attachment	Screwed
EF001454 - Sealable	false
EF001613 - Circuit integrity	None
EF005032 - With screening	false

EF004969 - Max. conductor cross section 2,5 mm²

EF004902 - Luminaire hook mounting false

EF008076 - Nozzle Other

EF005060 - With nail lugs false

EF006205 - Special application None