


Duplo Isolamento



## CARACTERÍSTICAS GERAIS

Em conformidade com a norma EN 60670-1  
Para montagem de embutir  
Fabricadas em material isolante termoplástico  
Cor: branco RAL 9010  
Entradas/saídas: cabos flexíveis e tubos lisos ou corrugados  
Classe II de isolamento na versão com tampa  
Índice de proteção IP20 (IP40 com tampa), IK07  
Sem halogéneos

## CARACTERÍSTICAS TÉCNICAS



|                                                      |                                       |
|------------------------------------------------------|---------------------------------------|
| Marca                                                | TEV                                   |
| Icons                                                | IP20, IK07, RAL9010, Duplo Isolamento |
| EF000003 - Mounting method                           | Concrete building                     |
| EF000051 - Shape                                     | Round                                 |
| EF000767 - Construction type                         | Cable junction box                    |
| EF000010 - Model                                     | Single                                |
| EF009204 - Provided with revolving ring              | false                                 |
| EF001229 - Connectable                               | true                                  |
| EF000557 - Equipped with                             | None                                  |
| EF000551 - Diameter                                  | 42,5 mm                               |
| EF000049 - Depth                                     | 35 a 35 mm                            |
| EF004508 - Mounting switching equipment              | Screwing                              |
| EF005066 - With screws                               | false                                 |
| EF009763 - Housing feed-through by break-out opening | true                                  |
| EF009206 - Housing feed-through by seal membrane     | false                                 |
| EF009207 - Housing feed-through by nozzle            | false                                 |
| EF009208 - Housing feed-through by step membrane     | false                                 |
| EF005496 - For tube diameter                         | 20 mm                                 |
| EF005466 - Suitable for cable diameter               | 1,5 a 2,5 mm                          |
| EF005657 - Pipe locking                              | false                                 |
| EF009209 - Pipe locking optional                     | false                                 |
| EF005604 - Inlet from the rear                       | true                                  |
| EF003593 - Number of inlets                          | 2                                     |
| EF002169 - Material                                  | Plastic                               |
| EF000025 - Halogen free                              | true                                  |
| EF000139 - Surface protection                        | Untreated                             |
| EF000007 - Colour                                    | White                                 |
| EF005474 - Degree of protection (IP)                 | IP20                                  |
| EF009212 - Cover model                               | None                                  |
| EF011401 - Transparent cover                         | false                                 |
| EF004586 - Cover attachment                          | Screwed                               |
| EF001454 - Sealable                                  | false                                 |
| EF001613 - Circuit integrity                         | None                                  |
| EF005032 - With screening                            | false                                 |
| EF005430 - Air tight                                 | false                                 |

EF004969 - Max. conductor cross section 2,5 mm<sup>2</sup>

EF004902 - Luminaire hook mounting false

EF008076 - Nozzle Other

EF005060 - With nail lugs false

EF006205 - Special application None